

WE SEPARATE ACCORDING TO YOUR APPLICATION

Lab Blown Film Machine

Features:

- * Siemens PLC and touch screen control system, highly intelligent and easy to operate
- * Calender rolls and rolls independently driven by the brand traction motor
- * Calender roll and pinch roll, were plated by hard chrome and polished mirror
- * Winding adopts magnetic powder clutch to achieve constant tension winding

Application:

- * Performance testing of material blown film
- * Performance test of master batch dispersion
- * Film blowing process parameters optimization
- * Studies of film forming properties
- * Studies on pigment dispersibility

小型吹膜机

产品性能:

- * 触摸屏及siemens PLC集中控制系统, 高智能化, 操作方便
- * 牵引辊由品牌变频电机独立驱动
- * 牵引辊表面镀硬铬并镜面抛光处理
- * 恒张力收卷

应用范围:

- * 材料吹膜性能测试
- * 色母料分散性能测试
- * 吹膜生产工艺参数优化
- * 研究材料的吹膜成型性能
- * 研究颜料的分散性能



Technical Parameters / 技术参数:

Model / 型号	HTBS-20
Screw Diameter / 螺杆直径	20 mm
L/D Ratio / 长径比L/D	28
Max. Speed / 最高转速	120rpm
Max. Temp. / 最高温度	350°C
Temp. Control Accuracy / 温控精度	±1.0°C
Pressure Measuring Range / 熔体压力测量范围	0~35MPa
Traction Speed / 牵引速度	0~10m/min
Max. Width of Film Entrance / 薄膜最大折径	160mm
Weight / 重量	580kg
Dimension / 外形尺寸 L×W×H	2980×944×2630mm